

2010 Fastrak LM

Limited Motor Option



The Limited Motor option will be allowed only in 2010.

1. MOTOR

Motor violations may result in fine and/or suspension. Weight limits may be adjusted during the season for competition.

ALL CARS—V8 motors only. Motor must be based on factory design and naturally aspirated. **1** spark plug and **2** valves per cylinder. **No** titanium or exotic metals except titanium retainers—OK. **No** fuel injection, turbo chargers or blowers.

Limited **2,400** weight—**358** cubic inch limit. **Cast** iron block. **No** Bow Tie blocks. **World** Products #0011150 or #012150, Bow Tie #14011034 or #12480034 heads only. **Vortec #25534371** and **#25534351** are NOT allowed. **No** porting or polishing heads except port matching $\frac{3}{4}$ " from the intake manifold interface and $\frac{3}{4}$ " depth valve seat cleanup/blending. **60cc** minimum combustion chamber. **Aluminum** intake—OK. **Flat** tappet cam only. **No** mushroom or roller lifters. **Stud** mounted roller rockers—OK. **Flat** top or inverted pistons with zero deck clearance. **Steel** crank with **3.480** maximum stroke. **No** lightening of crank. **Any** rods permitted. **2.100** rod pins. **25 $\frac{1}{2}$ "** setback from center of the ball joint to the front of the motor plate.

2. CARBURETOR

One **2** or **4** barrel carburetor permitted.

3. DISTRIBUTOR

Limited **2,400** weight—**MSD** with 6400 RPM chip required.

4. SPOILERS

Spoiler measurements may be adjusted during the season for competition.

ALL CARS—Spoiler and braces must meet all specifications listed on diagram. **72"** maximum width. **Maximum 3** solid side spoilers permitted. **Side** spoilers must be mounted at rear of deck and outer side spoilers must be at outside edge of deck. **Side** spoiler must taper down evenly from maximum to minimum height and may be rounded or triangular in shape. **2** additional **1"** open aluminum braces permitted. **Spoiler** should be clear lexan or aluminum. **No** driver-adjustable spoilers. **Spoiler** must be mounted at rear of deck. **Spoiler** may not be suspended to create a wing. **No** other spoilers or wings.

Limited **2,400** weight—**4"** maximum vertical spoiler height measured from top of rear deck and **6"** maximum spoiler length measured along the angle of the spoiler. **8"** maximum side spoiler height from rear of side spoiler to **6"** forward of rear of side spoiler. **4.5"** maximum height at front of side spoiler. **18"** maximum side spoiler length.

All other Fastrak LM rules apply!